

THE BOLD NEW AGE



D-MAX

Specifications:
ISUZU D-MAX 3.0 Ddi V-CROSS A/T

www.isuzu.co.za    

ISUZU
With you, for the long run

ISUZU D-MAX 3.0 Ddi V-CROSS A/T

ENGINE	
Engine Code	4JJ3
Displacement (cc)	2 999
No. of Cylinders	4
Compression Ratio	16.3:1
Bore X Stroke (mm)	95.4 X 104.9
No. of Valves	16
Power (kW) @ r/min	140 @ 3 600
Torque (Nm) @ r/min	450 @ 1 600 – 2 600
Turbocharger	Standard
800 mm Water Depth Protection	Standard
Pre-Air Cleaner	Standard
ACG (90 A)	Standard
ACG with with Intelligent Battery System (IBS)	Standard
Intercooler	Standard

FUEL CONSUMPTION ¹	
Combined Cycle (Litres/100 km)	7.9
Combined CO ₂ Emissions (g/km)	208
Fuel Type	Diesel

TRANSMISSION	
Transmission Type	6-Speed Automatic
Gear Ratio: 1st	3.600
Gear Ratio: 2nd	2.090
Gear Ratio: 3rd	1.488
Gear Ratio: 4th	1.000
Gear Ratio: 5th	0.687
Gear Ratio: 6th	0.580
Gear Ratio: Reverse	3.732
4WD Selector	-
Low Range Ratio	-

FRONT DIFFERENTIAL	
Shift on the Fly up to 100 km / hour	-
Axle Ratio: Final Drive	3.727

REAR DIFFERENTIAL	
Differential Lock	Standard
Axle Ratio: Final Drive	3.727

CHASSIS DESIGN	
Front Wheel Suspension	Coil Over Shock
Rear Wheel Suspension	Leaf Spring Overslung
Shock Absorbers	Twintube Gas Pressurised
Suspension	High-Ride
Skid Plate Guard Front	Standard
Skid Plate Guard Rear	Standard
Engine Sump Guard	Standard
Transfer Case Guard	-
Oil Pan Guard	Standard

WHEELS AND TYRES	
Tyre Size	265 / 60 R 18
Wheels Size / Type	Alloy 18" X 7.5J-33
Spare Wheel Size / Type	Alloy 18" X 7.5J-33
Turning Circle (m)	12.5
Tyre-Pressure Monitoring Sensor	Standard

DIMENSIONS	
Length (mm)	5 333
Width (mm)	1 880
Height (mm)	1 810
Wheelbase (mm)	3 125
Front / Rear Track (mm)	1 570 / 1 570
Rear Overhang (mm)	1 318
Ground Clearance (mm)	232
Loadbox Length (mm)	1 495
Loadbox Width (mm)	1 530
Loadbox Depth (mm)	490
Approach Angle (°)	30
Departure Angle (°)	18
Breakover Angle (°)	22.5
Wading Depth (mm)	800

MASS / CAPACITY	
Gross Axle Mass – Front (GA1) (kg)	1 450
Gross Axle Mass – Rear (GA2) (kg)	1 910
Gross Vehicle Mass (GVM) (kg)	3 000
Gross Combined Mass (GCM) (kg)	6 000
Tare Mass (kg)	1 980
Payload (kg)	960
Towing Capacity (kg): Unbraked Trailer ²	750
Towing Capacity / Rating (kg): Braked Trailer ²	3 500
Fuel Tank Capacity (Litres)	76

LOADBOX FEATURES	
Tiedown Brackets in Loadbox for Load Restraint	4
Rope Hooks on Loadbox Side	-

SAFETY FEATURES	
Anti-Lock Braking System (ABS)	Standard
Electronic Brake-Force Distribution (EBD)	Standard
Brake-Assist System (BAS)	Standard
Electronic Stability Control (ESC) with Traction Control	Standard
Hill-Start Assist (HSA)	Standard
Hill-Descent Control (HDC)	Standard
Trailer Sway Control	Standard
Brake-Override Accelerator (BOA)	Standard
Multi-Collision Brake	Standard
Height-Adjustable 3-Point Front Seatbelts	Standard
Front Seat Centre Lap Belt (2-Point)	-
Seatbelt Pre-Tensioners	Standard
Fixed 3-Point Rear Seatbelts	Standard
Seatbelt Reminder	Driver and Passenger
Occupant Detection Sensor	Front and Rear Passengers
Driver and Passenger Airbags	Standard
Front Seat Side Airbags	Standard
Curtain Airbags	Standard
Knee Airbag	Driver
Far Side Airbag	Standard
Side-Impact Protection Bars	Standard
Improve Side-Pole Impact	-
Collapsible Steering Column	Standard
Speed-Sensitive Door Lock	Standard
ISOFIX Child-Seat Attachment	Standard with Top Tether
Parking Distance Sensors	Front and Rear
Rear-View Camera	Standard
Front Camera	Standard
Warning Triangle Kit	Standard
Emergency Stop Signal	Standard
Blind-Spot Monitor	Standard
Rear Cross-Traffic Alert	Standard
Rear Radar	Standard
Autonomous Emergency Brake	Standard
Forward-Collision Warning	Standard
Pedal Misapplication Mitigation	Standard
Manual Speed Limiter	Standard
Lane-Departure Warning	Standard
Lane-Keep Assist	Standard
Lane-Departure Prevention	Standard
Driver Monitoring	Standard

SECURITY FEATURES	
Manual Door Locks	-
Remote-Controlled Central Locking	-
Remote Keyless Entry	-
Passive Entry Start System (PRESS)	Standard
Child-Proof Rear Door Locks	Standard
Anti-Theft Alarm System	Standard
Ultrasonic Alarm	Standard
Transponder Immobiliser System	Standard
Selectable Door Unlock	Standard
Walk-Away Auto Door Lock	Standard

INTERIOR / EXTERIOR LIGHTING	
Front Reading Lamps	Standard
Interior Courtesy Lamps	Standard
Illuminated Entry	Standard
Front Fog Lamps	Standard / LED
Daytime Running Lights (DRL)	LED
Headlamps	LED
Headlamp Levelling	Automatic
Headlamps 'ON' Warning Buzzer	Standard
Automatic On/Off Headlamp	Standard
Automatic High Beam	Standard
Turn Indicator Lamp on Door	-
Rear Taillights – Combination	LED
High-Mounted Centre Stop Lamp	Standard
Rear Fog Lamps	Standard
Follow-Me-Home Headlamps	Standard

EXTERIOR FEATURES	
Front Wiper	Auto / Rain-Sensing
Radiator Grille	Gun Metallic
Front Bumper	High Appearance
Rear Bumper	Body Colour
Front Bumper Cladding	Standard Gun Metallic
Towbar	Standard (3.5T)
Exterior Door Handle	Dark Grey Metallic
Exterior Mirror	Gun Metallic, Power Adjustment and Folding, Heated, Side Indicator, Driver Side Aspherical
B-Pillar Blackout	Standard
Over Fender (Fender Flares)	Standard Gun Metallic
Roof Rails	Standard
Sports Bar	-
Sports Hoop	Standard Gun Metallic

Side-Steps	Standard Medium Grey
Mudflaps	Front and Rear
Tailgate Handle	Dark Grey Metallic

INTERIOR FEATURES	
Power-Assisted Steering (PAS)	Electric
Air Conditioning	Automatic, Dual Zone
Pollen Filter	Standard
Inside Rear-View Mirror	Auto Dimming
Sunvisor	Driver and Passenger with Vanity Mirror Light
Overhead Console with Map Lamps (X2) and Sunglasses Holder	Standard
Digital Clock	Standard
Cruise Control	Standard, Adaptive
Multi-Information Display (MID)	Standard
Dashboard Illumination Control	Standard
Power Socket – Auxiliary 12V IP Mounted	1
Cigarette Lighter	Standard
Lockable Glove Box	Standard
Utility Box on Glove Box	Standard – High Type
Steering Column Adjustment	Tilt and Telescopic
Steering Wheel Trim	Leather
Steering Wheel Multi-Functional Controls	Audio, SAS, Auto Cruise and Adaptive Cruise Control
Gear Shift Trim	Leather with Decorate
Rear Seat Configuration	Bucket Seats (x2)
Rear Seat Configuration	60:40 Split-Cushion Bench
Seat Trim	Partial Leather
Seat Adjustment	8-Way Power Driver, Power Lumbar Support Driver
Storage Pockets behind Front Seats	Standard
Door Trim with Storage Pockets and Integrated Cupholders	Standard
Interior Door Release Handle	Chrome
Interior Trim Colours	Black Upper / Black Lower
A-pillar Assist Grip – Driver and Passenger	Standard
Roof-Mounted Assist Grips	Driver and Passengers
Floor Trim	Carpet with Heel Pad and Tibia Pad
Floor Tunnel Console with Integrated Cupholder	Standard
Centre Console Storage Box with Lid	Standard with Soft Pad with Stitch
Driver Footrest	Standard
Rear Heater Duct	-
Rear Ventilation Duct	Standard
Storage Box	-
Window Operation	Power Front and Rear with Driver One-Touch, Jam Protection and Timer
Rear Window	Fixed with Defogger
Fuel Flap Remote Opener	Standard
Ventilator Grille with Shutter (Fin Shut)	Standard

INFOTAINMENT	
Audio System	AM/FM Radio, 9" Touchscreen, Bluetooth® – Audio Streaming, Apple CarPlay® & Android Auto, Wi-Fi & Hands-Free Phone
USB Port (Music Playback and Device Link)	Standard
USB Charge Port	Rear
Speakers	8
Antenna	Standard

OPTIONS	
17" Alloy Wheel	-
18" Alloy Wheel and 265 / 60 R 18 Tyre (All Terrain)	-
18" Alloy Wheel and 265 / 60 R 18 Tyre (H/T Terrain)	Available
Differential Lock	-
Hubcap Steel Wheel	-
Hubcap Alloy Wheel	-
Spare Tyre Steel	-
Spare Tyre Alloy	-
Sports Bar – Black	-
Sports Bar – Chrome	-
Rear Sliding Window	Available
Partial Leather Seat with Manual Adjustment	-

WARRANTY / SERVICE INTERVALS	
Warranty and Roadside Assistance	5 Years / 120 000 km
Anti-Corrosion Warranty	5 Years / Unlimited km
Service Plan	5 Years / 90 000 km
Service Intervals	12 Months / 15 000 km

¹ Fuel Economy and CO₂ data as per ECE R101 / SANS 20101 regulation. Note that the actual fuel consumption will depend on many factors, including the driver's driving habits, prevailing conditions and the vehicle's equipment, condition and use.

² Towing capacity subject to South African Road Traffic Act. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle and trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 and GA2) must not be exceeded (e.g.: if a 3.0L Diesel is towing 3,500kg, its maximum Vehicle mass is 2,500kg in order to be within GCM).