

N-SERIES

Specification Sheet

NLR 150



www.isuzu.co.za f t

ISUZU

With you, for the long run

MODEL	NLR 150
AXLE LAYOUT	4X2
CONTROL	FORWARD
MASS	
Permissible Body + Payload (kg)	2260
Tare - Total (T) (kg)	1940
Tare - Front (kg)	1390
Tare - Rear (kg)	550
GVM (kg)	4200
V (kg)	4200
GCM (kg)	7050
D/T (kg)	7050
Axle - Front GA/GAU (kg)	2900
Axle - Front A/AU (kg)	1950
Axle - Rear GA/GAU (kg)	5000
Axle - Rear A/AU (kg)	3700
Litres of Fuel Tank 1 Included in Tare (litres)	15
Litres of Fuel Tank 2 Included in Tare (litres)	0
Tools Included in Tare	Jack, Warning Triangle, Basic Tool Kit
Spare Wheel Included in Tare	Yes
PERFORMANCE	
Gradeability at V (%)	52
Gradeability at D/T (%)	31
Max. Geared Road Speed (km/h)	133
MAJOR DIMENSIONS	
OL - Overall Length (mm)	4730
OW - Overall Width (mm)	1770
WB - Wheelbase (mm)	2475
CA - Cab to Bogie/Rear Axle (mm)	2022
CE - Cab to End of Chassis (mm)	3167
OH - Overall Height (mm)	2150
FOH - Front Overhang (mm)	1110
ROH - Rear Overhang (mm)	1145
EH - Chassis Rear End Height (mm)	760
HH - Ground Clearance (mm)	200

MODEL	NLR 150
AXLE LAYOUT	4X2
CONTROL	FORWARD
MAJOR DIMENSIONS	
Chassis Width - Rear (mm)	700
Turning Radius - Curb to Curb (mm)	5250
Turning Radius - Wall to Wall (mm)	5800
ENGINE	
Make	Isuzu
Model	4JJ1-TC
Capacity (cm ³)	2999
Layout	Diesel Inline-4
Type	Turbocharged Intercooled Common Rail
Power @ r/min (kW)	96 @ 2800
Torque @ r/min (Nm)	330 @ 1600 - 2600
Emissions Standard	Euro 2
CLUTCH	
Make	Exedy
Model	300
Type	Single
Diameter (mm)	300
Operation	Hydraulic-Assisted
TRANSMISSION	
Make	Isuzu
Model	MYY5T
Type	5-Speed Synchronesh
Shift	Manual Gearshift
No. of Gears Forward	5
First Gear Ratio : 1	5.315
Top Gear Ratio : 1	0.721
Transfer Case	No
PTO (Power Take-Off)	Optional
DRIVE AXLE	
Make	Isuzu
Model Axle Front	F029

MODEL	NLR 150
AXLE LAYOUT	4X2
CONTROL	FORWARD
DRIVE AXLE	
Model Drive Axle Rear	R045
Reduction Type	Single
Final Ratio : 1	4.100
SUSPENSION	
Front	Semi-Elliptic Springs
Rear	Semi-Elliptic Springs
Shock Absorbers	Front & Rear
Stabilisers	Yes
STEERING	
Operation	Power
BRAKES	
System Type	Vacuum Hydraulic
Front	Discs
Rear	Drums
Anti-Lock Braking System (ABS)	Standard
Park / Emergency System	Drum on Propshaft
Exhaust Brake	Standard
ELECTRICAL & FUEL	
Fuel Tank 1 Capacity (litres)	75
Fuel Tank 2 Capacity (litres)	0
TYRES	
Size & Ply Rating - Front	195 / 75 R16C
Size & Ply Rating - Rear	195 / 75 R16C
CAB & EXTRAS	
Type	Day
Roof	Low
No. of Bunks	0
No. of Seats (Lap, Rear & Centre)	3
Air-Conditioning	Optional
Radio	Optional
Tilt Cab	Yes

The information above is provided as a guide only. Specification is subject to change at any time. Please contact your nearest dealer to confirm current specification. Model/s shown may differ. E&OE. Date of print January 2018.